

Noncontact AC Calorimetry of Liquid Silicon with Suppressed Convections in a Static Magnetic Field

H. Kobatake,^{C,S} H. Fukuyama, I. Minato and T. Nakamura

Institute of Multidisciplinary Research for Advanced Materials (IMRAM), Tohoku University, Aoba-ku,

Sendai, Japan

kobatake@tagen.tohoku.ac.jp

T. Tsukada

Graduate School of Engineering, Department of Material Science and Engineering, Osaka Prefecture University, Sakai, Osaka, Japan

S. Awaji

Institute for Materials Research (IMR), Tohoku University, Aoba-ku, Sendai, Japan

Thermal transport properties of liquid silicon, such as heat capacity, total hemispherical emissivity, and thermal conductivity, are important parameters used in computer simulations for the growth of a single high quality, large diameter silicon crystal. However, these properties have not been well determined because of the existence of contamination from the container and of convections under gravity. In order to overcome these problems, noncontact AC calorimetry with suppressed convections has been developed.

Liquid silicon was levitated by the electromagnetic levitation technique in a vacuum. The convection in the levitated silicon was suppressed by the static magnetic field of 0 to 4 T generated by a superconducting magnet. The liquid silicon was periodically heated by a semiconductor laser. The temperature response of the liquid silicon was measured by a two-color pyrometer. The experiment was conducted in the temperature range between 1700 and 2050 K.

The molar heat capacity of liquid silicon was obtained from the temperature amplitude. The total hemispherical emissivity and thermal conductivity were obtained from the phase difference between the laser power and temperature response signals. The average values of the heat capacity and the total hemispherical emissivity are $28.2 \pm 3.3 \text{ J}\cdot\text{K}^{-1}\cdot\text{mol}^{-1}$ and 0.28 ± 0.03 respectively, and their temperature dependences are negligible in this temperature region. The apparent value of the thermal conductivity is decreased with increasing static magnetic field up to 2 T. However, the thermal conductivity converged on the value of $62.4 \pm 5.3 \text{ W}\cdot\text{m}^{-1}\cdot\text{K}^{-1}$ for a static magnetic field of 2 to 4 T. This result suggests that the convection has been suppressed and is negligible, leading to accurate measurement of the thermal conductivity.

This study was subsidized by the Japan Keirin Association through its Promotion funds from KEIRIN RACE and was supported by the Mechanica, Social Systems Foundation and the Ministry of Economy, Trade and Industry of Japan.